

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

WATTAGE

SPECIFICATIONS

ENVIRONMENTAL

CONTENT BACKING FINISH WEIGHT WIDTH ROLL SIZE

* 80% polyester acrylic latex CryptonWall® 'Green' 14 oz. 54" 50 yards

* 20% olefin Soil & Stain

Repellant

46% RECYCLED CONTENT

· 11% post-consumer (polyester)

Passes: UBC 8-2 Corner Burn

· 35% post-industrial (15% polyester, 20% olefin)

FLAMMABILITY

Class A / ASTM E-84

FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 100,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) Class 5.0 / 40 hrs.

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenguard Gold Certified

- · Number 23850-410
- · formerly Children & Schools Gold Certified
- · meets Calif 1350 High Performance Schools



^o Hytex, Inc. 2017 All rights reserved.

©2017 CRYPTON, Inc. CRYPTON and the planet logo are registered trademarks of CRYPTON, Inc. U.S. patent 5,565,265 and other U.S. and global patents issued and pending.

REPREVE is a registered trademark of Unifi, Inc.