

The trusted classic. We love the simplicity of our functional fabric-wrapped acoustic panels. Call it like it is, right? The go-to solution for controlling reverb in any space, these come in various standard sizes and are offered in several thickness options to accommodate all budgets.

Don't Mess with A Good Thing, Perfect It.

Meticulously crafted like your future depends on it, because it does.



Specifications


Product Name	Dimensional Panel			
Design	Aspen, Bubbles, Currents, Dunes, Infinity, Linear, Ripple, Sand Dunes, Silhouettes, Steps, Waves			
Content	6–7lb 56% recycled fiberglass board with layered, tackable, high-impact resistant facers, 100% post-consumer recycled polyester fabric			
Thickness	Standard: 1" & 2", and 3"			
Width	See sizing guide on next page.			
Height	See sizing guide on next page.			
Weight	1" = .8 lbs/sq ft, 2" = 1.5 lbs/sq ft			
Edge Options	Square			
Sound Performance	ASTM C423-17: NRC 1" = 0.83 and 2" = 1.03			
Fire Performance	ASTM 84 Class A			
Environmental	Low VOC emissions, woven fabrics are FR (Flame Retardant) Free and Compliant with CAL AB 2998.			
Maintenance	Vacuum to remove any loose dirt or dust. You may use a soft or plastic bristle brush to loosen it. Avoid excess pressure. Compressed air can also be used to dust the material in difficult or large installations. Remove ordinary dirt and smudges with a mild soap and water solution and a clean, soft cloth or towel. Dry with a soft lint-free cloth or towel. A melamine magic eraser can be used for more difficult stains. Always apply any cleaning methods to a small area first to test effectiveness and result.			
Warranty	5 years			
Unit of Sale	Per square foot			


Sizes

Dimensional Panel Design	2x2	2x4	4x4	4x8	Continuous Pattern	Notes
Linear		~		✓		
Steps	~	✓	✓		✓	
Infinity	~	~	~		\checkmark	2" Reveal standard, no reveal available (slight modification to pattern to accommodate).
Silhouettes		~	~			Two 4x4 panels create the full 4x8 pattern. Panels should not be ordered as standalone panels.
Waves		✓	~		✓	Continuous Pattern is up to 4'x8' and then repeats.
Dunes	\checkmark	~	~			
Sand Dunes	~	~	~			
Currents	~		~		~	
Aspen	~	~	~			
Ripple	\checkmark		~		\checkmark	2" Reveal standard, no reveal available (slight modification to pattern to accommodate). Continuous only across 4 panels.
Bubbles	~		✓			

Construction & Hardware


Rotofast snap-on anchor













Z Clip








Test Results

1" Fabric Flat Panel


Absorption Coefficiency vs. Freq (Hz)



Freq (Hz)	Absorption Coefficiency
160	0.16
250	O.37
500	O.88
1000	1.09
2000	1.01
NRC	0.84

2" Fabric Flat Panel

Absorption Coefficiency vs. Freq (Hz)



Freq (Hz)	Absorption Coefficiency
160	0.72
250	O.93
500	1.11
800	1.11
1250	1.07
2000	1.02
3150	1.01
NRC	1.03

The Noise Reduction Coefficiency (NRC) is calculated as the arithmetic average of the absorption coefficients in the shaded bands only (250, 500, 1250 & 2000 Hz).

ASTM C 423-17: The specimens were tested in a Type A mounting, as defined by ASTM Practice B 795-05. Specimens were placed directly on the reverb room floor. The specimens had a 1" aluminum frame butted against them with the frame duct taped to the floor.





Standard Fabrics

Prime Time

