

tapetex wall materials

SPECIFICATION GOLDEN FLAX 68-2020/-2024
Collection 5 colors from Tapatex 68-Linen

Physical Properties

Surface Composition 100% Linen, flat woven and piece dyed.

Backing Paper backing of 70% woodpulp reinforced with 30% polyester.

Width 137 cm = 54"

Weight Approx. 890 gr/lm = 28.7 oz/lyd

Thickness Approx. 0.90 mm

Hanging Random

Precision trimmed for butt-joining by professional paper hangers.

Installation advice supplied with every roll.

Adhesive Adhesive Tapatex PRO-1 or similar premixed, heavy duty, clear vinyl

adhesive, suitable for textile wallcovering

Variation There can be a variation between sample material and finished product.

Stock cuttings are available for approval.

Performance See detailed results on our website.

Surface Finish A stain repellent finish prevents waterbased splashes penetrating and

staining the material.

Periodic vacuuming is recommended to prevent dust from building up on

the material surface.

Lightfastness Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest

LRV Values Testing as per BS 8493:2008+A1:2010, Datacolor DC500

Fire Rating ASTM E84 Class 1 or A and EUROCLASS (B s1 d0)

Permeability Rating Test result 55.3 as per ASTM E96-12, Method B, Water Vapor Transmission. ASTM D6196, D5197 and D5116, Environmental Chamber Test. The test

followed UL 2821 "Greengaurd Certification Program Method for Measuring

and Evaluating Chemical Emissions"

Reach SVHC Compliant as per Centexbel testing.

DoP # (CPR 305/2011), DOP-CPR-01

Sustainability

Linen is made from a plant, a 100% renewable natural resource.

The backing is FSC certified, FSC A000531.

In production, all energy sources are either green, wind or hydro based and all processes are waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

Supply and Packing

Delivery from stock by the full linear meter or full linear yard. The average piece length of this quality is approx. 30 linear meters or 33 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length. The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes, which are also made out of FSC certified wood pulp.

Harmonized System as per the World Customs Organization and Origin

Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands