

JEMMA™

de novo® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		20.0 oz./LY	619 G/PLM
		13.3 oz./SQ	451 G/PSM
	Fabric Type	Poly Cotton Osnaburg	
	Material Width	52/54"	
	Repeat	Horizontal 27" x Vertical 24"	

**Federal Specifications:** Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 15 Passes NFPA 286 Corner Burn Test

**Performance Features:**

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

MADE IN USA

**Environmental Attributes:**

- Ultra-low emitting – Pass rating under CA 01350

**Permeability, Moisture and Mold:** Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

de novo® WALL

**INSTALLATION NOTE**  
JEMMA™ is a random match, reversible pattern.  
For specifications and hanging instructions go to:  
[www.surfacematerials.com](http://www.surfacematerials.com)

**WBE**  
Women-Owned Business Enterprise

 **surface materials**  
The ultimate in interior finish products.

**(440) 248-0000**  
6655 parkland boulevard  
solon, ohio 44139  
(440) 519-1950 fax  
[www.surfacematerials.com](http://www.surfacematerials.com)

Copyright© 2021. All Rights Reserved  
Any copying or other use is expressly  
prohibited DeNovo Wall is a trademark.

  
**SUSTAINABILITY  
STANDARD**  
NSF/ANSI 342

  
Qualified  
Distributor