

**SPECIFICATION**                      **TERRAL 67-1740/-1749**, a multi-layer quality  
Collection                                10 colors from Tapatex 67-Nonwoven

## **Physical Properties**

---

Surface Composition                      70% FSC certified woodpulp, 20% Polyester, and 10% Sisal Fibres.  
Backing                                      Paper backing of 70% woodpulp reinforced with 30% polyester.  
Width                                        137 cm = 54”  
Weight                                        Approx. 360 gr/lm = 11.6 oz/lyd  
Thickness                                    Approx. 0.50 mm  
Hanging                                      Random.  
Precision trimmed for butt-joining by professional paper hangers.  
Installation advice supplied with every roll.  
Adhesive                                    Adhesive Tapatex PRO-1 or similar premixed, heavy duty, clear vinyl  
adhesive, suitable for textile wallcovering  
Variation                                    There can be a variation between sample material and finished product.  
Stock cuttings are available for approval.

## **Performance**                              See detailed results on our website.

---

Surface Finish                              A stain repellent finish prevents waterbased splashes penetrating and  
staining the material.  
Periodic vacuuming is recommended to prevent dust from building up on  
the material surface.  
Lightfastness                              Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest  
LRV Values                                    Testing as per BS 8493:2008+A1:2010, Datacolor DC500  
Fire Rating                                    ASTM E84 Class 1 or A and EUROCLASS (B s2 d0)  
Permeability Rating                        Test result 93.8 as per ASTM E96-12, Method B, Water Vapor Transmission.  
Indoor Air Quality                         ASTM D6196, D5197 and D5116, Environmental Chamber Test. The test  
followed UL 2821 “Greengaurd Certification Program Method for Measuring  
and Evaluating Chemical Emissions”  
Reach SVHC                                 Compliant as per Centexbel testing.  
DoP #                                         (CPR 305/2011), DOP-CPR-01

## **Sustainability**

---

The nonwoven is FSC certified, FSC A000531.  
In production, all energy sources are either green, wind or hydro based and all processes are  
waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

## **Supply and Packing**

---

Delivery from stock by the full linear meter or full linear yard. The average piece length of this quality  
is approx. 50 linear meters or 55 linear yards. However, as is common within the textile industry , it  
is not possible to establish a standard roll length. The wallcovering is reeled on to a cardboard core,  
wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual  
cardboard boxes or tubes, which are also made out of FSC certified wood pulp.

## **Harmonized System as per the World Customs Organization and Origin**

---

Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands